

HDL 600 up to 600 kg bearing load



Variably extensible:
500 – 2000 mm !!!
Shock absorbing wheels
for every ground type
incl. parking brake



Easy to dismantle
Optional in Aluminium
transport box



For elements up to
200 mm thick
With widening fixture,
even up to 250 mm pane
thickness!

A very low
centre of gravity
guarantees a safe stance



Panes up to 600 kg

A dismantling and adjustable glass transporter which can carry a large variety of pane sizes. For transport of panes up to 6,000 x 3,400 mm and 600 kg. The installation point of the pane can be variably adjusted in 2 dimensions. A very low centre of gravity guarantees a safe stance. A single man can thus manoeuvre panes even through doorways. Rubber tyres provide an easy, joltless drive. The wagon can be turned on a point. In just a few minutes it can be dismantled and stored in a small case.

Model	HDL 600
Bearing load	600 kg
Weight	52 kg
Transport	Packed in crate for car/ HGV
Operation	Single operator
Dimensions:	
L x B x H in mm:	2000 x 790 x 1980 mm
Width	110 mm - with widening fixture up to 250 mm
Length	Variably extensible 500 - 2000 mm
Height of upper cross rail	Various height settings 220 mm 620 mm 1030 mm 1820 mm
Wheel diameter	200 mm, optional 140 / 160
Clearance of pane	120 mm, optional down to 80 mm depending on wheel diameter
Deployment	partly drivable on terrain
Delivery in:	Wooden crate
Optionen	<ul style="list-style-type: none"> • Widening fixture up to 250 mm • Pane tip safeguard (top) • Additional pole buffers • Aluminium transport crate

GLASS TRANSPORT WAGONS